In the Claims

1-55. (Cancelled)

56. **(Currently Amended)** A method comprising:
receiving a plurality of time slots, wherein

 said time slots comprise a first frame and a second frame,

 said second frame is received subsequently to said first frame, and

 said first frame and said second frame are time-division multiplexed frames;

relocating existing network management information of said second frame from a set of

 byte locations of said second frame to another set of byte locations of said second

 frame;

relocating network management information from a first set of byte locations of said first

 frame to said set of byte locations of said second frame; [[and]]

cross-connecting said time slots;

selecting at least one of said time slots;

receiving a plurality of incoming time slots;

sequentially writing said incoming time slots into a plurality of input buffers;

randomly reading a plurality of outgoing time slots from said input buffers; and

outputting said outgoing time slots.

57.-58. (Cancelled)

60. (Previously Presented) The method of claim 56, further comprising:
extracting said network management information; and
routing said network management information.

61. **(Previously Presented)** The method of claim 60, wherein said cross-connecting
comprises[[:]] **said selecting said at least one of said time slots.**

 ~~selecting at least one of said time slots.~~

       Application No.: 09/727,905

62.   (**Previously Presented**) An apparatus comprising:

means for receiving a plurality of time slots, wherein

> said time slots comprise a first frame and a second frame, said second frame is
>
> > received subsequently to said first frame, and
>
> said first frame and said second frame are time-division multiplexed frames;

means for relocating existing network management information of said second frame

> from a set of byte locations of said second frame to another set of byte locations
>
> of said second frame;

means for relocating network management information from a first set of byte locations

> of said first frame to said set of byte locations of said second frame; [[and]]

means for cross-connecting said time slots;

means for selecting at least one of said time slots;

means for receiving a plurality of incoming time slots;

means for sequentially writing said incoming time slots into a plurality of input

> **buffers;**

means for randomly reading a plurality of outgoing time slots from said input

> **buffers; and**

means for outputting said outgoing time slots.

63-65. (**Cancelled**)

66.   (**Previously Presented**) The apparatus of claim 62, further comprising:

means for extracting said network management information; and

means for routing said network management information.

67.   (**Currently Amended**) The apparatus of claim 66, wherein said means for cross-

connecting comprises[[:]] **said means for selecting.**

~~means for selecting at least one of said time slots.~~

68.   (**Currently Amended**) A computer program product comprising:

a first set of instructions, executable on a computer system, configured to receive a

> plurality of time slots, wherein

said time slots comprise a first frame and a second frame,

said second frame is received subsequently to said first frame, and

said first frame and said second frame are time-division multiplexed frames;

a second set of instructions, executable on said computer system, configured to relocate network management information from a first set of byte locations of said first frame to said set of byte locations of said second frame;

a third set of instructions, executable on said computer system, configured to cross-connect said time slots[[,]] ;

a fourth set of instructions, executable on said computer system, configured to select at least one of said time slots;

a fifth set of instructions, executable on said computer system, configured to receive a plurality of incoming time slots;

a sixth set of instructions, executable on said computer system, configured to sequentially write said incoming time slots into a plurality of input buffers;

a seventh set of instructions, executable on said computer system, configured to randomly read a plurality of outgoing time slots from said input buffers; and

an eighth set of instructions, executable on said computer system, configured to output said outgoing time slots; and

computer readable storage media, wherein said computer program product is encoded in said computer readable storage media.

69.-71 (Cancelled)

72. (Currently Amended) The computer program product of claim 69, further comprising:

a ~~fourth~~ ninth set of instructions, executable on said computer system, configured to extract said network management information; and

a ~~fifth~~ tenth set of instructions, executable on said computer system, configured to select at least one of said time slots.